




A DOVER COMPANY



**COUPLINGS for
CLINICAL DIALYSIS
SYSTEMS**



SMC: Compact design; polypropylene version with EPDM seals provides chemical resistance

Material: Acetal, polypropylene, polycarbonate

Termination Sizes: 1/8 NPT or 1/16" – 1/8" hose barb

Feature: Smallest coupling; twist to connect



PLC: Suitable for small to medium size water line connections; mates with metal LC couplings

Material: Acetal

Termination Sizes: 1/4" - 3/8" hose barb or NPT pipe thread

Feature: General purpose coupling ; metal thumb latch



PLC12: EPDM seal is suitable for use with acid, bicarbonate and chemical sanitizers; mates with metal LC couplings

Material: Polypropylene

Termination Sizes: 1/4" - 3/8" hose barb or NPT pipe thread

Feature: Chemically-resistant coupling



APC: All plastic coupling for small to medium size water lines

Material: Acetal

Termination Sizes: 1/4" - 3/8" hose barb or NPT pipe thread

Feature: Plastic-latched coupling



Pictured: NS2

NS2, NS4, NS6: Non-spill design for safe, secure connections

Material (NS2): Glass-filled polypropylene

Termination Sizes: 1/8" – 1/4" hose barb or 1/8" NPT pipe thread

Feature: Compact design

Material (NS4): Glass-filled polypropylene, ABS

Termination Sizes: 1/8" – 3/8" hose barb

Feature: Plastic, non-spill design

Material (NS6): Glass-filled polypropylene

Termination Sizes: 3/8" – 1/2" hose barb

Feature: Higher flow, non-spill design



MPC: Small to medium size coupling with Class V or Class VI seal material options

Material: Medical-grade ABS, polycarbonate and polysulfone

Termination Sizes: 1/4" and 3/8" hose barbs, non-valved only

Feature: Medical-grade coupling



HFC12: For larger fluid lines that require chemical resistance such as spent dialysate lines or acid and bicarbonate connections


HFC35: For larger raw or RO water lines; includes female garden hose thread termination for connection to water spigots

Material: HFC12: Polypropylene (as shown)

HFC35: Polysulfone (white)

Termination Sizes: 3/8" – 3/4" hose barb or NPT pipe thread

Feature: High flow family of couplings



Not to scale.


DRUMQUIK® PRO: Secure, easy-to-use connection to acid or bicarbonate concentrate and sanitizer drums

Material: Food grade, virgin polypropylene and polyethylene

Termination Sizes: 3/8" – 3/4" hose barb, 1/2" NPT or 3/4" BSPP.

Fits 2" buttress or BCS 56x4 threaded drum bungs.

Feature: Integrated dip-tube and drum closure



Pictured: UDC

Not to scale.

FLEXIBLE PACKAGING: Provide closed connection to bag-in-box chemical packaging; insert/cap with connector body

Material (Puncture Seal): Polyethylene (LDPE) and polypropylene

Termination Sizes: 1/4" - 3/8" hose barb - cap fits 38mm bag-in-box thread-on spout

Feature: Puncture seal coupling

Material (UDC): Polypropylene

Termination Sizes: 3/8" – 3/4" hose barb

Feature: 38mm threaded cap

CLINICAL DIALYSIS APPLICATIONS

Used in chemical and water applications worldwide, high performance CPC quick disconnect couplings are used in dialysis clinics on a wide variety from systems—from the acid and bicarbonate lines to the water lines used on reverse osmosis (RO) water treatment systems. Save time reconnecting pipe threads and tubing onto fixtures and hose barsbs by installing high quality CPC quick disconnect couplings. CPC's non-spill and valved connections eliminate or minimize drips and spills.

- ✔ Larger clinics use a distribution system to produce the necessary fluids and chemicals in bulk on site. The distribution system delivers these systems from the mixing and water treatment systems in the back of the clinic to the dialysis machines. CPC panel mount couplings make machine set up fast and simple.

DIALYSIS EQUIPMENT >>

Quick disconnect couplings are a great solution for connecting dialysis machines to acid, bicarbonate, RO water and chemical waste service lines or containers.* Tubing and piping internal to the dialysis machine which require frequent connect/disconnect cycles can also be fitted with couplings for ease of maintenance. With tubing hose barb connections as small as 1/16" and pipe threads as small as 1/8" NPT, there are a wide range of coupling sizes.

ACID/BICARBONATE LINE CONNECTIONS:

Polypropylene PLC12 with EPDM seals work well in this environment.

RO WATER LINE CONNECTIONS: Polysulfone HFC35 with EPDM seals are excellent couplings for this application.


CHEMICAL WASTE LINE CONNECTIONS:

Polypropylene HFC12 with EPDM seals work well in this type of connection.

SMALL TO MEDIUM LINES INTERNAL TO DIALYSIS EQUIPMENT:

SMC in acetal, polypropylene or polycarbonate; APC in acetal; MPC in medical-grade ABS, polycarbonate or polysulfone are good choices for your system design.


**Some dialysis OEM's require use of proprietary couplings for service connections.*



Smart fluid handling to take you forward, faster.

DISTRIBUTION SYSTEMS

Biomedical technicians (“biomed techs”) who service dialysis equipment, RO water treatment systems and dialyzer reprocessing equipment save time and money by using the right couplings to disconnect equipment from acid, bicarbonate, RO water and disinfectant service lines. Replacement tubing, piping, pumps and tank vent filters are brought on line rapidly using quick disconnects to minimize down time.



ACID/BICARBONATE MIXING SYSTEM

Pumps and tank vent filters are easily replaced when fitted with quick disconnect couplings. The DrumQuik® PRO drum connector provides a safe, closed connection to concentrated liquid acid or bicarbonate drums.



ACID/BICARBONATE PUMPS AND LINE CONNECTIONS:

Polypropylene HFC12 with EPDM seals are a good choice for your system design.

ACID/BICARBONATE TANK VENT FILTER CONNECTIONS:

Polypropylene PLC12 with EPDM seals work well in this environment.

DISPENSING LINE CONNECTIONS TO DRUMS: Polypropylene DrumQuik® PRO with EPDM seals are excellent couplings for this application.

WATER TREATMENT SYSTEMS >>

Many RO systems already make use of PLC quick disconnect couplings to attach to pre-filtered water lines and down stream pumps, tanks or dialysis machines. Larger systems are quickly isolated or recycled for flushing or sanitizing purposes by using HFC35 couplings. Dispensing sanitizing chemistries to water systems are also facilitated by using polypropylene PLC12 couplings.

RO WATER LINE CONNECTIONS: Acetal PLC with Buna-N seals or polysulfone HFC35 with EPDM seals are a good choice for your system design.

SANITIZING CHEMICAL CONNECTIONS:

Polypropylene PLC12 and DrumQuik® PRO with EPDM seals are excellent couplings for this application.






« ON-SITE DIALYZER REUSE REPROCESSING

Quick connects on dialyzer water flush manifolds and reuse reprocessing equipment quickly and securely connect the dialyzer filter element to reprocessing equipment, or to connect reprocessing equipment to chemical bag-in-box containers or service lines.

DIALYZER QUICK CONNECTS: APC in acetal, or MPC in ABS, polycarbonate or medical-grade polysulfone work well in this environment.

CHEMICAL BAG-IN-BOX CONNECTIONS: Polypropylene Puncture Seal (PS) or UDC are excellent connectors for this application.



PORTABLE SYSTEMS RE-CHARGING AND MAINTENANCE »

By modularizing equipment with quick disconnect couplings, portable RO, carbon tanks and dialysis equipment are quickly and easily swapped out for repair and preventative maintenance or off-site re-charging. Automatic shutoff valves minimize spillage during changeovers.



ACID/BICARBONATE AND CHEMICAL WASTE LINE CONNECTIONS: Polypropylene PLC12 with EPDM seals work well in this environment.

RO WATER LINE CONNECTIONS: PLC with Buna-N seals are a good choice for your system design.



CPC's products are used across a broad range of medical devices and equipment, including surgical, dialysis, blood pressure monitoring, patient therapy devices, and in vitro diagnostics. A de facto standard in several applications, CPC connectors improve patient safety, prevent misconnections and increase the overall usability and effectiveness of medical devices. Medical device OEMs around the world choose CPC connectors because of our proven performance in the operating room, the life science lab, and the home healthcare setting.

COLDER PRODUCTS COMPANY
1001 WESTGATE DRIVE
ST. PAUL, MINNESOTA 55114
U.S.A.

PHONE: +1 651-645-0091
FAX: +1 651-645-5404
TOLL FREE: 800-444-2474

info@cpcworldwide.com
cpcworldwide.com

COLDER PRODUCTS COMPANY GMBH
OSTRING 19
D-63762 GROSSOSTHEIM
GERMANY

PHONE: +49-6026-9973-0
FAX: +49-6026-9973-173

cpcgmbh@cpcworldwide.com
cpcworldwide.com

COLDER PRODUCTS COMPANY LIMITED
FLAT B, 29/F, WEST GATE TOWER,
7 WING HONG STREET, CHEUNG SHA WAN
KOWLOON, HONG KONG

PHONE: +852-2987-5272
FAX: +852-2987-2509

asiapacific@cpcworldwide.com
cpcworldwide.com

CPC WARRANTY STATEMENT: CPC (Colder Products Company) warrants its products against defects in workmanship and materials for a period of 12 months from the date of sale by CPC to its initial customer (regardless of any subsequent sale of the products). This warranty is void if the product is misused, altered, tampered with or is installed or used in a manner that is inconsistent with CPC's written recommendations, specifications and/or instructions, or fails to perform due to normal wear and tear. CPC does not warrant the suitability of the product for any particular application. Determining product application suitability is solely the customer's responsibility. CPC is not liable for special, indirect, incidental, consequential or other damages including, but not limited to, loss, damage, personal injury, or any other expense directly or indirectly arising from the use of or inability to use its products either separately or in combination with other products. ALL OTHER WARRANTIES EXPRESS OR IMPLIED, WHETHER ORAL, WRITTEN OR IN ANY OTHER FORM, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY EXCLUDED. The sole and exclusive remedy under this warranty is limited, at the option of CPC, to replacement of the defective product or an account credit in the amount of the original selling price. All allegedly defective CPC products must be returned prepaid transportation to CPC, together with information describing the product's application and performance, unless otherwise authorized in writing by CPC.

CPC PATENT STATEMENT: CPC takes pride in its innovative quick disconnect coupling and fittings solutions, many of which have been awarded United States and international patents. CPC has a strong tradition of leadership in the quick disconnect market, and aggressively pursues and protects its proprietary information and intellectual property. In cases where it is practical and has a benefit to its customers, CPC has licensed its proprietary technology. Please contact CPC to discuss your unique needs.

CPC TRADEMARK STATEMENT: AseptiQuik®, BottleQuik®, BreakAway®, ChemQuik®, DrumQuik®, FitQuik®, IdentiQuik®, Nu-Seal®, SnapQuik®, Steam-Thru®, Softube® are registered trademarks with the U.S. Patent & Trademark Office. All other trademarks or service marks are property of their respective owners. **WARNING:** Due to the wide variety of possible fluid media and operating conditions, unintended consequences may result from the use of this product, all of which are beyond the control of CPC. It is the user's responsibility to carefully determine and test for compatibility for use with their application. All such risks shall be assumed by the buyer.

WARNING: Due to the wide variety of possible fluid media and operating conditions, unintended consequences may result from the use of this product, all of which are beyond the control of CPC. It is the user's responsibility to carefully determine and test for compatibility for use with their application. All such risks shall be assumed by the buyer.

